

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 March 2005 (24.03.2005)

PCT

(10) International Publication Number  
**WO 2005/026604 A1**

(51) International Patent Classification<sup>7</sup>: **F16L 55/165**,  
B29C 65/34 // 63/30, 53/36

(21) International Application Number:  
PCT/GB2004/003944

(22) International Filing Date:  
15 September 2004 (15.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0321636.3 16 September 2003 (16.09.2003) GB

(71) Applicant and

(72) Inventor: **CHANDLER, Brian** [GB/GB]; 48 Waterloo  
Road, Bedford MK40 3PG (GB).


(74) Agent: **BAILEY WALSH & CO LLP**; 5 York Place,  
Leeds LS1 2SD (GB).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GI, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: LINING OF PIPELINES AND PASSAGEWAYS



(57) Abstract: The invention relates to the formation of a tube (34) and the provision of the tube (34) to line a host pipe and hence repair and/or strengthen the same. The tube is formed of a web (10) of material to which at least one wire strip (18) is applied such that when the web (10) of material is introduced into the host pipe, the at least one wire strip is located at the overlapping longitudinal edges of the web (10). The tube (34) is expanded to the internal size of the host pipe and electric current applied to the wires in the wire strip (18) to heat the same and bond the overlapping edges together.

WO 2005/026604 A1



**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*